


PRODUCT DATA SHEET



A) SPECIFICATIONS

- 1 Calibrated twin black saddles made in H.D.P.E
- 2 Stainless steel threaded bar BFI M8
- 3 Stainless steel pressure plate PSAL
- 4 Stainless steel hexagonal nut DAI 8
- 5 Stainless steel flat Washer REI 8
- 6 Stainless steel pressure plate PUC 70

B) RESISTANCE TESTS

UV Test BS-ISO 105-B06
Vibration test conforming to UNI 60068-2-6
Operating temperature: -30°C +120°C

C) PACKAGING INFORMATION

Packing in boxes.
Label indicating:
product code, article, quantity,
production batch,
FIMO logo and figure.
(Customer code on request).

D) MOUNTING INSTRUCTIONS

On request

CODE	ARTICLE	Ø D	L	h	H	BOX	WEIGHT
61 1565 4012	LCL/ 4x1/2"	15 - 17	62	100	54	20	235
61 1565 4078	LCL/ 4x7/8"	27 - 29	84	125	79	20	260
61 1565 4114	LCL/ 4x1.1/4"	38 - 40	102	150	103	20	330
61 1565 4158	LCL/ 4x1.5/8"	50 - 52	119	200	125	20	400

RI	DATE	DR	DATE	AP	Description: LCL - LCO+2 PUC 70 steel pressure plate • Side Insertion of Cables • Elastic Prefixing • Manual Final Locking
02					
01					
00	03/11/2015	G.S.	03/11/2015	A.V.	
1 ST EMISSION					
					Use: Fastening of 4 cables on steel wire cable trays