


PRODUCT DATA SHEET



A) SPECIFICATIONS

- 1 Stainless steel bow
Hooking on flat and round 3-12mm
- 2 Self-locking pressure screw M6
- 3 Stainless steel sliding pressure plate.
- 4 DAS/DAT black P.A. saddles

B) RESISTANCE TESTS

UV Test BS-ISO 105-B06
Vibration test conforming to UNI 60068-2-6
Operating temperature: -30°C +120°C

C) PACKAGING INFORMATION

Packing in boxes.
Label indicating:
product code, article, quantity,
production batch,
FIMO logo and figure.
(Customer code on request).

D) MOUNTING INSTRUCTIONS

IST026

CODE	ARTICLE	ø D	L	H	WEIGHT
61 1582 0305	mRF B/ 3x5	4 - 5	12	55	48
61 1582 0306	mRF B/ 3x6	5 - 6	12	55	48
61 1582 0307	mRF B/ 3x7	6 - 7	12	55	48
61 1582 0308	mRF B/ 3x8	7 - 8	12	55	48
61 1582 0309	mRF B/ 3x9	8 - 9	12	55	42
61 1582 0310	mRF B/ 3x10	10 - 11	12	55	42
61 1582 0312	mRF B/ 3x1 1/2" (17)	16 - 17	22	91	130
61 1582 0378	mRF B/ 3x7/8" (28)	27 - 28	34	128	231

RI	DATE	DR	DATE	AP	Description: Stainless cable clamps type mRF B For 3 coaxial cables, complete with 3 calibrated saddles. For articles see schedule.
02					
01					
00	29/01/16	G.S.	29/01/16	A.V.	
1 ST EMISSION					
					Use: Fastening of 3 coaxial cables. Hooking on flat and round 3-12mm

FI.MO.TEC. S.p.a. reserves the right to modify the technical specifications without prior notice, according to the technical progress
Copyright FI.MO.TEC. S.p.a. All rights reserved.